

Step by Step Guide >	1 Installation >		2 Sampling Method >			3 Well Diameter >		4 Typical Depth Range				Material Type	Nominal Size (OD inches)	Standard Tubing (OD inches)
	Dedicated	Portable	Low Flow	Well Volume	No Purge	≤ 1" (25 mm)	2" + (50 mm)	0 to 100' (0 to 30 m)	100 to 200' (30 to 60 m)	200 to 500' (60 to 150 m)	500' + (150 m)			
407 Bladder Pump	●	●	●	●			●	●	●	●		SS	1	1/4 Dual
							●	●	●	●			1.66	1/4 Dual
							●	●					PVC	1.66
408 Double Valve Pump	●	●	●	●		●	●	●	●	●		SS	5/8	1/4 Dual
							●	●	●	●			1.66	1/4 Dual
							●	●					PVC	1.66
408M Micro Double Valve Pump	●	●	●	●		●	●	●	●		PTFE	3/8	3/8 & 3/16 Coaxial	
425 Discrete Interval Sampler		●			●		●	●	●	● to 300' (90 m)		SS	1, 1.66, 2	1/4
425-D Deep Sampling Discrete Interval Sampler		●			●		●	●	●	● to 4000' (1200 m)		SS	1.66	1/4
410 Peristaltic Pump		●	●	●		●	●	●				N/A	N/A	1/4 & 1/2
415 12V Submersible Pump	●	●	●	●				● to 120' (35 m)				ABS	1.88	1/2
428 BioBailer™	Single Use			●			●	●				Biodegradable PVC	1.5	N/A
			●	●	●				3/4					
429 Point Source Bailer	●	●		●	●	●	●	●				SS	0.5, 1, 1.5, 2	N/A
404 Inertial Pump	●		●	●		●		●	●			SS	0.17	1/4
						●	●	●	●			D16	5/8	5/8
							●	●	●			D25	1	5/8
						●	●	●	●			SS16	5/8	5/8
							●	●	●			SS19	3/4	5/8